Linking Resilience and Robustness and Uncovering their Tradeoffs in Coupled Infrastructure Systems

Mehran Homayounfar¹, Rachata Muneepeerakul¹, John M. Anderies², and Chitsomanus P. Muneepeerakul³

¹Department of Agricultural and Biological Engineering, University of Florida, Gainesville, Florida, USA
 ²School of Sustainability and School of Human Evolution and Social Change, Arizona State University, Tempe, Arizona, USA
 ³Independent researcher, Gainesville, Florida, USA

Correspondence to: Mehran Homayounfar (homayounfar@ufl.edu) and Rachata Muneepeerakul (rmuneepe@ufl.edu)

- 10 Abstract. Robustness and resilience are concepts in systems thinking that have grown in importance and popularity. For many complex social-ecological systems, however, robustness and resilience are difficult to quantify and the connections and trade-offs between them difficult to study. Most studies have either focused on qualitative approaches to discuss their connections or considered only one of them under particular classes of disturbances. In this study, we present an analytical framework to address the linkage between robustness and resilience more systematically. Our
- 15 analysis is based on a stylized dynamical model that operationalizes a widely used conceptual framework for socialecological systems. The model enables us to rigorously delineate the boundaries of conditions under which the coupled system can be sustained in a long run, define robustness and resilience related to these boundaries, and consequently investigate their connections. The results reveal the trade-offs between robustness and resilience. They also show how the nature of such trade-offs varies with the choices of certain policies (e.g., taxation and investment in public
- 20 infrastructure), internal stresses and uncertainty in social-ecological settings.

1. Introduction

The concepts of "resilience" and "robustness" have grown considerably in popularity as desirable properties for a wide range of systems. Terms like "resilient communities" and "robust cities" have been used more frequently in public discourse (e.g., Chang and Shinozuka, 2004; Longstaff et al., 2010; Chang et al., 2014). The UK's Water Act

- 25 2014 even included "primary duty to secure resilience" as one of the general duties of its Water Services Regulation Authority (Water Act, 2014). Growing with that popularity is some confusion and potential misuse of the terms "robustness" and "resilience" due to imprecision, vagueness, and multiplicity of their definitions. Such lack of consistency and rigor hinders advances in our understanding of the interplay between these two important system properties.
- 30 Relatively speaking, robustness has been defined more consistently and rigorously—as it can be linked to a more familiar concept of sensitivity. For example, according to Carlson and Doyle (2002), robustness in engineering systems refers to the maintenance of system performance either when subjected to external disturbances or internal uncertain parameters. In other words, in robust systems, performance is less sensitive to disturbances or uncertainty.

Robustness may very well be a desirable property of a system, but it seems to come with a price. Recent research shows that tuning a system to be robust against certain disturbance regimes almost always reduces system performance and likely increases its vulnerability to other disturbance regimes (Ostrom et al., 2007; Anderies et al., 2007; Bode, 1945; Csete and Doyle, 2002; Wolpert and Macready, 1997). Now, if resilience is also a desirable property of the

- 5 same system, does it also come at the expense of performance and robustness? Put it another way, is there a trade-off among performance, robustness, and resilience? Such a trade-off, if exists, is a crucial consideration for governing and/or managing social-ecological systems (SESs).
- But resilience, as alluded to above, is trickier to define. According to Holling (1973), resilience refers to the amount of change or disruption required to shift the maintenance of a system along different sets of mutually reinforcing
 processes and structures. In other words, resilience can be thought of as how far the system is from certain thresholds or boundaries beyond which the system will undergo a regime shift or a quantitative change in system structure or identity. Holling (1996) categorized resilience into two types, engineering resilience, which refers to the ability of a system to return to steady state following a perturbation, and ecological resilience, which refers to the capacity of

system to remain in a particular stability domain in the face of perturbations. The latter category is used by many

- 15 researchers to discuss resilience of SESs, or more generally, *coupled infrastructure systems* (CISs) (Carpenter et al., 2001; Folke, S et al., 2002; Anderies et al., 2006; Folke, 2006; Folke et al., 2010; Biggs et al., 2012; Barrett and Constas, 2014; Redman, 2014; Walker et al., 2002; Gunderson et al., 1995; Berkes and Folke, 1998; Carpenter et al., 1999a, 1999b; Scheffer et al., 2000; Berkes et al., 2003; Walker et al., 2004; Carpenter and Brock, 2004; Janssen et al., 2004; Folke et al., 2002; Anderies et al., 2006; Folke et al., 2016; Cote and Nightingale, 2012; Mitra et al., 2015;
- 20 Cumming and Peterson, 2017). The term coupled infrastructure systems (CISs) has been introduced to generalize the notions of coupled natural-human systems (CNHSs) and social-ecological systems (SESs); in this context, *infrastructure* is broadly defined to include human-made, social, and natural infrastructure (see, e.g., Anderies et al., 2016). The problem is that these CISs are complex and thus identifying thresholds and potential regime shifts associated with those thresholds is often difficult, if not impossible. In many cases, major aspects of resilience in CISs
- 25 may not be directly observable and must be actualized indirectly via surrogate attributes (Carpenter et al., 2005; Kerner and Thomas, 2014). Recent significant advances have been made toward identifying early-warning signals that indicate whether a critical threshold is being approached for a wide class of systems (Scheffer et al., 2009 and 2012). Still, there are gaps in our understanding of how indicators of resilience and robustness will behave in more complex situations. This lack of a rigorous metric for resilience makes the investigation into their connections, interplay, and
- 30 trade-offs with robustness and performance impossible. But these knowledge gaps need to be filled if one wishes to make advances in understanding the interplay between social dynamics and planetary boundaries. Given the magnitude of impacts that human activities have on pushing Earth systems toward their planetary boundaries, we need clearer understanding of how social and biophysical factors come together to define the nature of these boundaries. This paper is a step in that direction. In particular, we will
- build on recent work that mathematically operationalizes the Robustness of SES framework (Anderies et al., 2004) into a formal stylized dynamical model (Muneepeerakul and Anderies, 2017). We will exploit the relative simplicity

of the model to rigorously define robustness and resilience of the coupled system. The modelled system will be subject to fluctuations in external drivers, which will affect the well-defined robustness and resilience, thereby enabling us to investigate the interplay and trade-offs between these important properties, as well as how the nature of the interplay and trade-offs are affected by policies implemented by social agents.

5 2. Methods

Here we analyse a mathematical model developed by Muneepeerakul and Anderies (2017) by subjecting the coupled system to uncertainty in ecological and social factors. The model captures the essential features of a system in which a group of agents shares infrastructure to produce valued flows. Such a system is the archetype of most, if not all of human sociality: groups produce infrastructure that they cannot produce individually (security, defence, irrigation

- 10 canals, roads, markets, financial systems, coordination mechanisms, etc.) that significantly increases productivity. The challenge is maintaining this shared infrastructure (e.g. decaying infrastructure is a major problem in the US at the time of writing (ASCER CIA Advisory Council, 2013). The model allows for mathematical definitions of the boundaries of policy domain that result in a sustainable system in which both human-made and natural infrastructure can be maintained over the long run. Based on these boundaries and uncertainty in the exogenous factors, we define metrics of resilience and robustness associated with each policy choice and investigate the trade-off between them.
- The basic model presented by Muneepeerakul and Anderies (2017) is described in the Appendix. Here a policy is defined as a combination of taxation level C and the proportion of tax revenue invested in infrastructure maintenance y that the public infrastructure providers (PIPs) decide to implement in the system. The infrastructure (e.g. canals) enable resource users (RUs) to produce valued goods from a natural resource. The two
- 20 fluctuating exogenous factors are the replenishment rate of the natural resource g and the wage w that resource users (RUs) would earn from working outside the system—a combination of g and w defines a "social-ecological setting" or simply "setting." There are two boundaries that, once crossed, will cause the system will collapse. The first boundary is called PIP participation constraint (PPC): when the PIPs must invest too much in maintaining the public infrastructure (exceeding the opportunity cost of w_P) and/or cannot retain enough revenue for themselves, they will
- 25 abandon the system for another. The second boundary is the stability condition of the non-trivial equilibrium point (i.e., the "society" in which both PIPs (e.g. the state) and RUs (e.g. citizens) participate in the system and public infrastructure is sufficiently maintained in a long run). Together, these two boundaries delineate a set of policies (*Cy* combinations) that correspond to sustainable outcomes. The resilience metric to be developed below can be thought of as a metric of how far the system is from these boundaries. As the two exogenous factors defining settings, namely
- 30 g and w, fluctuate, the two boundaries and thus the resilience metric, too, fluctuate with them. How sensitive the resilience metric is to these fluctuating settings is used to define robustness. Here, it is worth noting that, while it is possible to examine recovery-based resilience (or the so-called "engineering resilience"), this paper focuses on regime shift-based resilience (traditionally called "ecological resilience") and its robustness. Quantification of and trade-offs between resilience and robustness is a novel concept that requires expositional clarity. Presenting several metrics of
- resilience, let alone studying their trade-offs with potentially different metrics of robustness, may confuse the matter

and dilute the key messages we attempt to convey. As such, in what follows, we will focus on developing a metric for regime shift-based resilience. With the scope of analysis clarified and suitably bounded, we will now define resilience and robustness more formally.

2.1. Resilience metric

25

- 5 Direct measurement of above-mentioned resilience, as a specified form of resilience (Walker et al., 2004), in SES's is difficult because boundaries and thresholds that separate domains of dynamics for SES's are difficult to identify (Carpenter et al., 2005; Scheffer et al., 2009 and 2012). In this stylized model, however, such boundaries can be clearly identified by the stability condition (SC) and the PPC. Here, we are interested in the resilience of system's ability to provide sufficient livelihoods for the PIPs and resource users. The basin of attraction for system resilience is defined
- 10 by those system states (i.e. infrastructure state) in which this is possible, and these system states are directly mapped to the SC and PPC. We will thus define resilience metrics based on the SC and PPC boundaries. Here our goal is to develop resilience metrics that can be meaningfully compared to one another. As such, we identify some desired properties that guide the definitions of these resilience metrics. First, they should be zero at their respective boundaries. Second, positive values indicate greater resilience of the system in a desirable state. These first two properties align
- 15 with how resilience has been measured, i.e., the distance from the boundary of a basin of attraction (e.g., Anderies et al., 2002; S. R. Carpenter et al., 1999). Third, to facilitate the consideration of relative risks associated with different types of regime shifts that the system may be facing, the metrics should be comparable in magnitude. These properties guide us toward the following definitions of the resilience metrics.

We define the resilience of the system against abandonment by PIPs as follows:

20
$$R_{PPC} = (\pi_{PIP}/w_P) - 1, (1)$$

where π_P is the net revenue that PIPs collect and w_P is the opportunity cost that they will earn if they choose to work with another system. Positive values of R_{PPC} indicate that the system is resilient against being abandoned by PIPs, while negative values indicate that the system will eventually collapse due to the PIPs' abandonment. It is important to note that π_P results from the coupled dynamics of the CIS; this means that R_{PPC} has already integrated the dynamics of infrastructure, resource, and resource users (Eqs. A1, A4 and A5), making it a metric of the system, not of an

individual component. Numerical analysis of the model indicates that the equilibrium becomes unstable when the following Routh-Hurwitz condition (e.g., May, 2001; Kot, 2001) is violated:

$$D - T(J_{1,1}J_{2,2} + J_{2,1}J_{1,2} + J_{2,3}J_{3,2} + J_{1,3}J_{3,1}) > 0, (2)$$

- 30 where, D, T, and J's are determinant, trace, and entries, respectively, of the Jacobian matrix of the dynamical system (Eqs. A1, A4, and A5) evaluated at the nontrivial equilibrium point (Eq. A6)—when such an equilibrium point exists. Here, it is worth noting that we focus on the equilibrium point related to the non-trivial sustainable long-term outcome. Analyzing other bifurcations related to other equilibria may be mathematically interesting, but it could make the study less accessible and dilute its key message about the resilience-robustness trade-off of different policies aiming at
- 35 keeping the system in the basin of attraction of the non-trivial sustainable long-term outcome.

Following the guideline provided by the three desirable properties above, we rearrange terms in Eq. (2) and define the resilience of the system against instability (increased probability of collapse of infrastructure) as follows:

$$R_{stability} = \frac{D}{\left|T\left(J_{1,1}J_{2,2} + J_{2,1}J_{1,2} + J_{2,3}J_{3,2} + J_{1,3}J_{3,1}\right)\right|} - 1,(3)$$

This formulation is parallel to that of the first resilience metric (Eq. 1); it possesses the three properties: $R_{stability}$ of zero indicates the boundary between stability and instability; positive $R_{stability}$ means the system at the equilibrium point is stable; and the magnitudes of $R_{stability}$ are comparable to those of R_{PPC} (see Fig. 1). Note that $R_{stability}$, too, is determined from the coupled dynamics of the CIS; this means that it has integrated the dynamics of infrastructure, resource, and resource users (Eqs. A1, A4 and A5).

This allows us to meaningfully define the overall system resilience as the minimum between the two resilience metrics, namely:

$$R_{system} = \begin{cases} Min[R_{PPC}, R_{Stability}], \land R_{PPC}, R_{stability} \ge 0\\ 0, \land otherwise \end{cases}, (4)$$

Equation (4) implies that R_{system} is positive only when the nontrivial equilibrium point (Eq. A6) exists and is stable; otherwise, the system is considered not resilient and denoted by $R_{system} = 0$. R_{system} thus represents the tension between the PIPs being too greedy (high C, low y) whereby they get close to the stability boundary and "not greedy enough," i.e., low C and high y whereby they get close to the PPC, given a particular choice for w_P . Note that the values of w and w_P represent the socio-economic embedding of the CIS. Therefore, the biophysical structure of the CIS along with the socio-economic context in which it is embedded co-determine the maximum resilience that can be achieved. Given that the nontrivial equilibrium point exists and is stable, if the system is at a greater risk of being abandoned by the PIPs (and eventually collapsing), $R_{system} = R_{PPC}$; if the system is at a greater risk of becoming unstable (and eventually collapsing), $R_{system} = R_{stability}$. Figure 1 illustrates the relationships between R_{PPC} ,

$R_{stability}$, and R_{system} .

10

Figure 1: Resilience metrics for a specific setting (a *g-w* combination) inside the sustainable region in the policy space (i.e., *C-y* plane): (a) *R_{PPC}* contours; (b) *R_{Stability}* contours; and (c) *R_{system}* contours. The black star in panels (a), (b), and (c) indicate the policy with the highest *R_{PPC}*, *R_{Stability}*, and *R_{system}*, respectively.

25 2.2. Linking Robustness and resilience

As discussed earlier, robustness can be thought of as the opposite of sensitivity. A commonly used measure of sensitivity is variance. Thus, variance of a given function under specific disturbance or uncertainty regimes may be used to indicate robustness of that function against those disturbance or uncertainty regimes (robustness of what to what). In this case, the system function of interest is the system resilience R_{system} . By choosing R_{system} as our function, we can usefully link these concepts. If we use a hall and cup metaphor for resilience, the robustness of

30 function, we can usefully link these concepts. If we use a ball and cup metaphor for resilience, the robustness of

resilience refers to the degree at which the geometry of the cup changes as a result of external disturbances and/or parameter changes. However, as we will argue below, relating high variance of R_{system} to low robustness may be misleading and should not be used in evaluating a given policy. By definition, the variance treats "good deviations" and "bad deviations" from the mean equally. For functions with preferred values, such as resilience or profit, values

- 5 greater than the mean and those lower should not be treated in the same way. Specifically, contribution to a high variance from a heavy tail in the good direction should not be translated to less robustness. This problem also arises in assessing financial risk: what makes an asset risky is the values on the "bad tail" of the distribution (i.e., low or negative profits). This has motivated more and more analyses to switch to considering other measures of risk, such as the conditional value at risk, in evaluating their portfolios of investment (Rockafellar and Uryasev, 1999; Krokhmal
- 10

25

0 et al., 2001; Sarykalin et al., 2008; Zymler et al., 2013). Intuitively, this means that the shape of the "cup" can be asymmetric and we need to take this into account.

Following this logic, we propose to use a "below-mean mean" as a new robustness metric: the mean of all resilience values lower than the mean. This new definition of the robustness metric has several desirable features. First, it can now be appropriately thought of as a robustness metric in the sense that the higher the value, the more robust the

- 15 system (unlike the variance for which low variance means high robustness). Second, by using the mean as the threshold value for bad deviations, we remove some arbitrariness associated with prescribing a certain quantile (e.g., 5th or 10th quantile) in calculating the conditional value at risk. Third, it still carries some information about the sensitivity of the resilience metric to outside factors—the information that variance conveys; that is, the higher the "below-mean mean" (i.e., the bad deviations from the mean are small and the below-mean mean is close to the mean), the less sensitive—and thus mere reduct to the resilience metric.
- 20 and thus more robust—the resilience metric.

In this study, we subject the modelled system to uncertainty in one natural factor and one social factor, namely, the natural replenishment rate of the resource g, and the payoff that a RU earns from working outside the system w. Thus, we are computing how the resilience of the system to shocks/variation in state variables changes as the parameters g and w change (i.e., we are uncertain about the underlying social-ecological setting of the system). In particular, we assume that g is uniformly distributed over the range [75, 125] and w is uniformly distributed over the range [0.75, 1.75]. A social-ecological setting, or setting, is defined as a combination of g and w. For a given policy (a C - y combination), we calculate R_{system} for 10,000 settings (i.e., 10,000 g - w combinations) (see Fig. 2). Then, from these 10,000 values of the resilience metric R_{system} , we calculate the mean, $\mu_{R-system} = E[R_{system}]$, and use it as the **resilience metric** of the coupled system with a given policy, and the below-mean mean, $\mu_{R<\mu} =$

30 $E[R_{system} \lor R_{system} < \mu_{R-system}]$, as the metric for robustness of resilience. This metric measures the robustness of the capacity of the system to cope with variation in state variables I_{HM} , R, and U to fundamental uncertainty about the underlying setting of the system.

Figure 2: Variation of R_{system} of a CIS with a fixed policy (C, y) over 10,000 settings associated with uncertainty characterized by $\{g \in [75,125], w \in [0.75,1.25]\}$: (a) R_{system} surface and (b) R_{system} contours. The values of R_{system} are used to calculate the mean, $\mu_{Rsystem}$, and the below-mean mean, $\mu_{R<\mu}$. In this particular case, the resilience does not change much when g is greater than about 100, but becomes more sensitive to both g and w when g is lower than 100.

3. Results

The surfaces and contours of the system resilience metric, $\mu_{Rsystem}$, and associated with different policies (C - y) over the policy space are shown in Figs. (3a and b), respectively. The policies with sustainable outcomes are located in the middle of the policy space, with $\mu_{Rsystem}$ peaking in the center and declining as policies become more extreme in either direction. Our analysis also shows that $\mu_{Rsystem}$ is more or less proportional to the fraction of settings (*g*-*w* combinations) under which the system with that particular policy (a *C*-*y* combination) results in a sustainable outcome ($R_{system} > 0$). A similar concept has been used in the robust decision making literature (e.g., Groves and Lempert, 2007; Bryant and Lempert, 2009).

The surfaces and contours of the robustness of, $\mu_{R < \mu}$, associated with different policies over the policy space are

15 shown in Figs. (3c and d), respectively. The $\mu_{R < \mu}$ "landscape" is more irregular, having two local maxima with one being more dominant than the other. The region with high robustness appears to be in the same general areas as the region with high resilience. These features reflect the nonlinear interplay between the model parameters and model structure and may affect the nature of the trade-off between robustness and resilience reported in Figures 4 and 5.

Figure 3: the mean, $\mu_{R-system}$, and the below-mean mean of R_{system} , $\mu_{R<\mu}$, over entire decision space: (a) 20 Surface of the resilience metric, $\mu_{R-system}$; (b) Contours of $\mu_{R-system}$; (c) Surface of the robustness, the belowmean mean ($\mu_{R<\mu}$); (d) Contours of the robustness, the below-mean mean ($\mu_{R<\mu}$)

We explore the interplay between $\mu_{Rsystem}$ and $\mu_{R<\mu}$ in Fig. 4. Figure 4 shows that there are no perfect policies in the sense that no policies yield both maximum resilience and maximum robustness. Recall that the robustness indicates how sensitive R_{system} itself is to uncertainty in the underlying setting of the system (e.g., g and w). The best policies are those along the Pareto frontier in the resilience-robustness space: among this set of Pareto-optimal policies, an increase in resilience is necessarily accompanied by a decrease in robustness, clearly illustrating the trade-off between robustness and resilience. Fig. 5 illustrates where the Pareto-optimal policies are located in the policy space.

Figure 4: Resilience-robustness trade-off. Each point represents, $\mu_{R-system}$ and $\mu_{R<\mu}$ of the coupled system with a given policy. The black dots represent a set of Pareto-optimal policies.

30 Figure 5: Pareto optimal policies, represented by black dots, in the policy space (C-y plane), superimposed with resilience $(\mu_{R-system})$ (a) and robustness $(\mu_{R < \mu})$ contours (b).

10

25

4. Discussion and conclusions

In this paper, we exploit the simplicity of a stylized model to quantitatively link resilience and robustness by computing how the CIS's resilience to shocks in state variables changes with parameters. In this way, we compute the robustness of CIS resilience to uncertainty in the underlying CIS setting. The resilience metric developed here is a measure of

- 5 how far the CIS is from the boundaries beyond which it will collapse. The model affords us with expressions of these boundaries, which clearly show how social and biophysical factors interplay to define these boundaries. With a concrete definition of resilience, resilience itself can be considered as the "of what" in the "robustness of what to what" notion. In particular, we use the below-mean mean of the quantitatively defined resilience metric as the metric of robustness. Consequently, this enables us to rigorously investigate the interplay between the two important, but not
- 10 always well-defined, system properties. A key finding is the fundamental trade-off between resilience and robustness: there are no perfect policies in governing a CIS, only Pareto-optimal ones. Specifically, policies designed to maximize the resilience of a CIS to shocks on timescales at which the state variables play out may be very sensitive to being wrong about our understanding of the underlying dynamics of the CIS in question.
- Importantly, we hope this work will stimulate further advances in rigorous studies of CISs that address such subtle,
 policy-relevant questions, a few of which we briefly discuss here. More dimensions can be considered in defining Pareto-optimality. Figure 5 may give an impression that the set of Pareto-optimal policies is confined to a small region in the policy space, which would imply that PIPs do not have that many choices—even in a simple CIS like the one studied. But that would be a wrong impression. In addition to resilience and robustness (as defined here), a policy maker or a social planner may be interested in other types of robustness with different "of what" and "to what"
 components. She may also be concerned about other system properties, e.g., productivity, user participation, etc. As more dimensions are considered, the set of Pareto-optimal policies grow. In the same spirit as that of the work done

here, these other dimensions should be defined rigorously.

This work also lends itself to more rigorous studies of "adaptive governance." In the present study, the governance structure, represented by a policy (a combination of C and y), is fixed. A natural next step is to explore if a policy is

- 25 allowed to change, how one may improve the resilience and robustness of a CIS and/or alter the nature of their inherent trade-offs. For example, if C and y are to be functions of other factors, e.g., resource availability and outside incentives, what functional forms should they take to improve the system's resilience and robustness? Indeed, in the absence of transparent metrics, attempts to explore such adaptive policies are severely limited.
- Additionally, agents in a CIS may have the capacity to change their behaviour in response to changes in policy,
 environmental conditions, technological changes, and the like. In this study, strategic behaviour and decision-making process are assumed unchanged in the analysis. Adaptation in strategic behaviour of agents will subsequently alter the nature of resilience, its robustness, and their trade-offs. Capturing such effects of adaptation requires structural changes to the model, e.g., in terms of specification of payoffs or even the formulation of the dynamical equations. With such adaptive social agents, how should one devise adaptive governance to enhance resilience and robustness of

a CIS? Addressing such a question is a theoretically intriguing future research direction with great practical implications.

In keeping with the theme of "social dynamics and planetary boundaries in Earth system modelling," our results shed light on how social and biophysical factors may interplay to define "boundaries" of a sustainable coupled infrastructure

5 system. While the modelled system here is admittedly simple, our methodology and results constitute a step toward quantitatively and meaningfully combining social and biophysical factors into indicators of boundaries of more complex systems. Just as in this work, once those boundaries are clearly defined, calculation and discussion of resilience and robustness can become concrete.

Author contribution: MH, RM, JMA, and CPM designed the study. MH carried out the analysis. MH and RM

10 prepared the manuscript with contributions from all co-authors.

Competing interests: The authors declare that they have no conflict of interest.

Acknowledgements: JMA and RM acknowledge the support from the grant NSF GEO-1115054. The authors also thank the editor and two anonymous referees for their constructive and useful comments.

5. Reference:

15 Anderies, John M., et al.: Grazing Management, Resilience, and the Dynamics of a Fire-Driven Rangeland System., Ecosystems, vol. 5, no. 1, pp. 23–44, doi:10.1007/s10021-001-0053-9, **2002**.

Anderies, J., Janssen, M., & Schlager, E.: Institutions and the performance of coupled infrastructure systems. International Journal of the Commons, 10(2), **2016**.

Anderies, J., et al.: A Framework to Analyze the Robustness of Social-Ecological Systems from an Institutional Perspective. Ecology and Society, <u>http://www.ecologyandsociety.org/vol9/iss1/art18/inline.html</u>, **2004**.

Anderies, J. M., et al.: Panaceas, Uncertainty, and the Robust Control Framework in Sustainability Science. Proceedings of the National Academy of Sciences, vol. 104, no. 39, pp. 15194–99, doi:10.1073/pnas.0702655104, **2007**.

 Anderies, John M., Paul Ryan, et al.: Loss of Resilience, Crisis, and Institutional Change: Lessons from an Intensive Agricultural System in Southeastern Australia. Ecosystems, vol. 9, no. 6, pp. 865–78, doi:10.1007/s10021-006-0017-1, 2006.

ASCE RCIA Advisory Council: Report card for America's Infrastrutre, Tech. Rep., American Society of Civil Engineers, **2013**.

Barrett, Christopher B., and Mark A. Constas.: Toward a Theory of Resilience for International Development
 Applications. Proceedings of the National Academy of Sciences, vol. 111, no. 40, pp. 14625–30, doi:10.1073/pnas.1320880111, 2014.

Berkes, Fikret, et al.: Navigating Social-Ecological Systems: Building Resilience for Complexity and change Building, p. 393, doi:10.1016/j.biocon.2004.01.010, **2003**.

Berkes, Fikret, and Carl Folke.: Linking Social and Ecological Systems for Resilience and Sustainability.
 Linking Social and Ecological Systems: Management Practices and Social Mechanisms for Building Resilience, vol. 1, pp. 13–20, 1998.

Biggs, Reinette, et al.: Toward Principles for Enhancing the Resilience of Ecosystem Services. Annual Review of Environment and Resources, vol. 37, no. 1, Nov, pp. 421–48, doi:10.1146/annurev-environ-051211-123836, **2012**.

Bode, Hendrik Wade.: Network Analysis and Feedback Amplifier Design. Bell Telephone Laboratories Series, p. 551, doi:10.1183/09031936.00138507, **1945**.

Bryant, Benjamin P., and Robert J. Lempert.: Thinking inside the Box: A Participatory, Computer-Assisted Approach to Scenario Discovery. Technological Forecasting and Social Change, vol. 77, no. 1, pp. 34–49, doi:10.1016/j.techfore.2009.08.002, **2010**.

Carlson, J. M., and J. Doyle.: Complexity and Robustness. Proceedings of the National Academy of Sciences, vol. 99, no. Supplement 1, pp. 2538–45, doi:10.1073/pnas.012582499, **2002**.

Carpenter, S., et al.: From Metaphor to Measurement: Resilience of What to What? Ecosystems, http://www.springerlink.com/index/lu5mxqkxbblkly62.pdf, 2001.

5

10 Carpenter, S. R., et al.: Management of Eutrophication for Lakes Subject to Potentially Irreversible Change. Ecological Applications, vol. 9, no. 3, pp. 751–71, doi:10.2307/2641327, **1999**.

Carpenter, Stephen R., William Brock, et al.: Ecological and Social Dynamics in Simple Models of Ecosystem Management. *Conservation Ecology*, vol. 3, no. 2, pp. 1–31, doi:10.5751/ES-00122-030204, **1999**.

Carpenter, Stephen R., Frances Westley, et al.: Surrogates for Resilience of Social-Ecological Systems.
 Ecosystems, vol. 8, no. 8, pp. 941–44, doi:10.1007/s10021-005-0170-y, 2005.

Carpenter, Stephen R., and William A. Brock.: Spatial Complexity, Resilience, and Policy Diversity: Fishing on Lake-Rich Landscapes. Ecology and Society, vol. 9, no. 1, **2004**.

Chang, Stephanie E., et al.: Toward Disaster-Resilient Cities: Characterizing Resilience of Infrastructure Systems with Expert Judgments. Risk Analysis, vol. 34, no. 3, pp. 416–34, doi:10.1111/risa.12133, **2014**.

20 Chang, Stephanie E., and Masanobu Shinozuka.: Measuring Improvements in the Disaster Resilience of Communities. Earthquake Spectra, vol. 20, no. 3, pp. 739–55, doi:10.1193/1.1775796, **2004**.

Cote, Muriel, and Andrea J. Nightingale.: Resilience Thinking Meets Social Theory. Progress in Human Geography, vol. 36, no. 4, pp. 475–89, doi:10.1177/0309132511425708, **2012**.

Csete, Marie E., and John C. Doyle.: Reverse Engineering of Biological Complexity. Science (New York, N.Y.), vol. 295, no. 5560, pp. 1664–69, doi:10.1126/science.1069981, 2002.

Cumming, Graeme S., and Garry D. Peterson.: Unifying Research on Social–Ecological Resilience and Collapse. Trends in Ecology and Evolution, vol. 32, no. 9, Elsevier Ltd, pp. 695–713, doi:10.1016/j.tree.2017.06.014, **2017**.

Folke, Carl.: Resilience: The Emergence of a Perspective for Social–ecological Systems Analyses. Global
Environmental Change, vol. 16, no. 3, Aug., pp. 253–67, doi:10.1016/j.gloenvcha.2006.04.002, 2006.

Folke, Carl, Steve Carpenter, et al.: Resilience and Sustainable Development: Building Adaptive Capacity in a World of Transformations. AMBIO: A Journal of the Human Environment, vol. 31, no. 5, p. 437, doi:10.1639/0044-7447(2002)031[0437:RASDBA]2.0.CO;2, **2002**.

Folke, Carl, Stephen R. Carpenter, et al.: Resilience Thinking: Integrating Resilience, Adaptability and
 Transformability. Ecology and Society, vol. 15, no. 4, doi:10.5751/ES-03610-150420, 2010.

Folke, Carl, Reinette Biggs, et al.: Social-Ecological Resilience and Biosphere-Based Sustainability Science. Ecology and Society, vol. 21, no. 3, doi:10.5751/ES-08748-210341, **2016**.

Groves, David G., and Robert J. Lempert.: A New Analytic Method for Finding Policy-Relevant Scenarios. Global Environmental Change, vol. 17, no. 1, pp. 73–85, doi:10.1016/j.gloenvcha.2006.11.006, **2007**.

40 Gunderson, Lance H., et al. Barriers and Bridges to the Renewal of Ecosystems and Institutions. Columbia University Press, **1995**.

Holling, C. S.: Resilience and Stability of Ecological Systems. Annual Review of Ecology and Systematics, vol. 4, no. 1, Nov, pp. 1–23, doi:10.1146/annurev.es.04.110173.000245, **1973**.

	Holling, Crawford Stanley.: Engineering Resilience versus Ecological Resilience. Engineering Within Ecological Constraints, no. 1996, pp. 31–44, doi:10.17226/4919, 1996 .
5	Janssen, Marco A., et al.: Robust Strategies for Managing Rangelands with Multiple Stable Attractors. Journal of Environmental Economics and Management, vol. 47, no. 1, pp. 140–62, doi:10.1016/S0095-0696(03)00069-X, 2004 .
	Kerner, David, and J. Thomas.: Resilience Attributes of Social-Ecological Systems: Framing Metrics for Management. Resources, vol. 3, no. 4, Multidisciplinary Digital Publishing Institute, pp. 672–702, doi:10.3390/resources3040672, 2014 .
	Kot, M.: Elements of Mathematical Ecology. Cambridge University Press, 2001.
10	Krokhmal, Pavlo, et al. Portfolio Optimization With Conditional Value-at-Risk Objective and Constraints. no. 352, pp. 1–30, 2001 .
	Longstaff, Patricia H. H., et al.: Building Resilient Communities: A Preliminary Framework for Assessment." Homeland Security Affairs, vol. 6, no. 3, pp. 1–23, 2010 .
	May, R. M.: Stability and Complexity in Model Ecosystems. Princeton university press, 2001.
15	Mitra, Chiranjit, et al.: An Integrative Quantifier of Multistability in Complex Systems Based on Ecological Resilience. Scientific Reports, vol. 5, Nature Publishing Group, pp. 1–10, doi:10.1038/srep16196, 2015 .
	Muneepeerakul, Rachata, and John M. Anderies. "Strategic Behaviors and Governance Challenges in Social- Ecological Systems." Earth's Future, vol. 5, no. 8, Wiley Periodicals, Inc., pp. 865–76, doi:10.1002/2017EF000562, 2017 .
20	Ostrom, E., et al.: Going beyond Panaceas. Proceedings of the National Academy of Sciences, vol. 104, no. 39, pp. 15176–78, doi:10.1073/pnas.0701886104, 2007 .
	Redman, Charles L.: Should Sustainability and Resilience Be Combined or Remain Distinct Pursuits? Ecology and Society, vol. 19, no. 2, p. art37, doi:10.5751/ES-06390-190237, 2014 .
	Rockafellar, R. Tyrrell, and Stanislav Uryasev. Optimization of Conditional Value-at-Risk, pp. 1–26, 1999.
25	Sarykalin, Sergey, et al. Value-at-Risk vs. Conditional Value-at-Risk in Risk Management and Optimization, pp. 270–94, doi:10.1287/educ.1080.0052, 2008 .
	Scheffer, Marten, Stephen R. Carpenter, et al.: Anticipating Critical Transitions. Science, vol. 338, no. 6105, pp. 344–48, doi:10.1126/science.1225244, 2012 .
30	Scheffer, Marten, Jordi Bascompte, et al.: Early-Warning Signals for Critical Transitions. Nature, vol. 461, no. 7260, Nature Publishing Group., pp. 53–59, doi:10.1038/nature08227, 2009 .
	Scheffer, Marten, William Brock, et al.: Socioeconomic Mechanisms Preventing Optimum Use of Ecosystem Services: An Interdisciplinary Theoretical Analysis. Ecosystems, vol. 3, no. 5, pp. 451–71, doi:10.1007/s100210000040, 2000 .
35	Walker, B., et al.: Resilience Management in Social-Ecological Systems: A Working\nhypothesis for a Participatory Approach. Conservation Ecology [Online], vol. 6, no. 1, p. 14, doi:14, 2002 .
	Walker, Brian, et al.: Resilience, Adaptability and Transformability in Social-Ecological Systems Resilience, Adaptability and Transformability in Social – Ecological Systems. Ecology and Society, vol. 9, no. 2, doi:10.5751/ES-00650-090205, 2004 .
40	Water act 2014, "Explanatory Notes have been produced to assist in the understanding of this Act and are available separately". CHAPTER 21, published by TSC (The Stationary Office) and available from: Online www.tsoshop.co.uk; (http://www.legislation.gov.uk/ukpga/2014/21/contents/enacted), 2014.
	Wolpert, David H., and William G. Macready.: No Free Lunch Theorems for Optimization. IEEE Transactions on Evolutionary Computation, vol. 1, no. 1, pp. 67–82, doi:10.1109/4235.585893, 1997 .

Zymler, Steve, et al.: Worst-Case Value at Risk of Nonlinear Portfolios. Vol. 59, no. 1, pp. 172–88, **2013**. APPENDIX

Basic model. Here we briefly describe the basic model presented by Muneepeerakul and Anderies (2017). The model shows dynamic behaviour of three principal variables, namely, the state of the public infrastructure, I_{HM} ,

5

resource level, R, and the fraction of time user makes use of infrastructure, U, through Eq's (A1, A4 and A5). The schematic diagram of this system of equations is shown in Figure A1.

Figure A1: Schematic diagram of the dynamical system model. Taken from Muneepeerakul and Anderies (2017). In this context, I_{HM} depends on PIPs in term of maintenance cost and has a positive relationship with the capacity of users to create resource flows. Eq. (A1) illustrates the dynamics of I_{HM} as follows:

10
$$\frac{dI_{HM}}{dt} = M(\dots) - \delta H(I_{HM}), \qquad (A1)$$

where, δ is the infrastructure's depreciation rate and $H(I_{HM})$ states functional relationship of public infrastructure and productivity of each resource user. According to Muneepeerakul and Anderies (2017) many shared infrastructures can be modelled by threshold functions. Given that $H(I_{HM})$ shows threshold behavior, they used a piecewise linear function to capture such behavior through Eq. (A2).

15
$$H(I_{HM}) = \begin{cases} 0, I_{HM} < I_0 \\ h \frac{I_{HM} - I_0}{I_m - I_0}, I_0 \le I_{HM} \le I_m, \\ h, I_{HM} \ge I_m \end{cases}$$
(A2)

where, h represents maximum amount of harvest by each user under no restriction and I_0 and I_m are lower bound and upper bound thresholds of I_{HM} respectively. Also, M(...) is maintenance function (Eq. A3) and depends on social structure of the system.

$$M(...) = \mu_2 y C p R U N H(I_{HM}), \tag{A3}$$

20 In Eq. (A3), given the number of users N, $RUNH(I_{HM})$ is the total harvest from the natural infrastructure. The resource users sell total harvest at price p to generate revenue. Subsequently, they assign a proportion C of revenue to PIP's for their contribution. Meanwhile, the PIP's spend proportion y of C on maintaining public infrastructure through the maintenance function M(...). Also, μ_2 is maintenance effectiveness of PIP's investment.

The second variable is resource level, R. They assumed the dynamics of resource to be:

$$\frac{dR}{dt} = G(R) - RUNH(I_{HM}) \tag{A4}$$

Natural infrastructure is assumed to invoke the conservation law comprising of regenerating capacity (G(R) = g - dR) and total unit of harvest, $RUNH(I_{HM})$. The definition presented for G is the simplest model for natural infrastructure where g and d are the natural replenishment and the loss rates, respectively.

5

20

The strategic behavior of the resource users (*RU's*) is captured by employing replicator equation. Indeed, replicator dynamics provide modeler with simple, realistic social mechanism where agents follow and replicate better-off strategies. The two possible strategies considered for RU's are staying inside system with the associated payoff of $\pi_U = (1 - C)pRH(I_{HM})$ or leaving system with the payoff of $\pi_w = w$. According to replicator equation:

$$\frac{dU}{dt} = rU(1-U)(\pi_U - w) \tag{A5}$$

Replicator equation discuss the fraction of time that RU's assign to working inside system given C and y. Like RU's, 10 there is also two alternatives for PIP's, working inside system or working for another CIS which leads to system failure. Meanwhile, C and y characterize the strategy or policy of PIPs. The PIPs will participate in this coupled system only when $\pi_p = (1 - y)pCRUNH(I_{HM}) \ge \pi_w$. In other words, the PIPs maintain in the system when they are better-off than working outside. This condition is termed the PIP Participation Constraint (PPC).

Based on the system of three differential equations (Eqs. A1, A4 and A5), the sustainable equilibria, i.e., long-term
system outcomes that satisfy the stability condition and PIP Participation Constraint (PPC), can be expressed as follows:

$$i_{HM}^{*} = \frac{yCU^{*}NR^{*}}{g}H(I_{HM}^{*}); R^{*} = \frac{g}{d}\left(1 - \frac{i_{HM}^{*}}{yC}\right); U^{*} = \frac{(1-C)}{yC}\phi_{1}i_{HM}^{*}, \tag{A6}$$

where $i_{HM}^* := \frac{l_{HM}^* \delta}{\mu_2 pg}$ (indicates dimensionless) and $\phi_1 = \frac{pg}{wN}$, a dimensionless group representing the relative lucrativeness of the system, namely the ratio of potential income—with the entire resource flow turned into income—relative to outside wage. The results reported in this study are based on the following parameter values: h = 0.0005; $\delta = 0.1$; $I_0 = 0.3$; $I_m = 3$; g = 100; d = 0.02; N = 1000; r = 0.15; p = 10; w = 1; $w_p = 100$; $\mu_2 = 0.001$.



Figure 1: Resilience metrics for a specific setting (a g-w combination) inside the sustainable region in the policy space (i.e., C-y plane): (a) R_{PPC} contours; (b) $R_{Stability}$ contours; and (c) R_{system} contours. The black star in panels (a), (b), and (c) indicate the policy with the highest R_{PPC} , $R_{Stability}$, and R_{system} , respectively.



Figure 2: Variation of R_{system} of a CIS with a fixed policy (C, y) over 10,000 settings associated with uncertainty characterized by $\{g \in [75,125], w \in [0.75,1.25]\}$: (a) R_{system} surface and (b) R_{system} contours. The values of R_{system} are used to calculate the mean, $\mu_{Rsystem}$, and the below-mean mean, $\mu_{R<\mu}$. In this particular case, the resilience does not change much when g is greater than about 100 but becomes more sensitive to both g and w when g is lower than 100.



14



Figure 3: the mean, $\mu_{R-system}$, and the below-mean mean of R_{system} , $\mu_{R<\mu}$, over entire decision space: (a) Surface of the resilience metric, $\mu_{R-system}$; (b) Contours of $\mu_{R-system}$; (c) Surface of the robustness, the belowmean mean ($\mu_{R<\mu}$); (d) Contours of the robustness, the below-mean mean ($\mu_{R<\mu}$)



Figure 4: Resilience-robustness trade-off. Each point represents, $\mu_{R-system}$ and $\mu_{R<\mu}$ of the coupled system with a given policy. The black dots represent a set of Pareto-optimal policies.



Figure 5: Pareto optimal policies, represented by black dots, in the policy space (C-y plane), superimposed with resilience $(\mu_{R-syste})$ (a) and robustness $(\mu_{R<\mu})$ contours (b).



Figure A1: Schematic diagram of the dynamical system model. Taken from Muneepeerakul and Anderies (2017).